مواصفات المنتج:

Parameter Sheet

Item		Parameter
OS		Linux
Language		Chinese/English/Customized
Video Compression		H.264
OSD		Overlays information such as date time and vehicle ID
GUI	Graphical User Interface	Setup system parameters with the remote control.
Video Record System	Video Input	4CH 720P AHD input/SD input/mixed video input,aviation connector, 1.0Vp-p, 75Ω
	Video Output	1CH CVBS+1CH VGA output, 1.0Vp-p, 75Ω,Aviation,Support 1CH Full Screen,4CH Screen
	Preview	Support 1 channel and 4 channels preview.,Support Manual/Alarm Trigger full screen preview
	Resolution	720P/D1/HD1/CIF, MAX:4 channels 720P
	Video Quality	0-7 levels, 0 is the highest level.
	Video Standard	PAL: 100f/s , CCIR625 line,50field; NTSC: 120f/s, CCIR525 line,60field; CIF: 256Kbps ~ 1.5Mbps, 8 level video quality optional; HD1: 600Kbps ~ 2.5Mbps, 8 level video quality optional; D1: 800Kbps ~ 3Mbps, 8 level video quality optional; 720P: 4Mbps-6Mbps, multi level video quality optional
	Record Mode	The default setting is auto recording after power on. Timed recording, alarm trigger recording and manual recording are supported.
Audio	Audio Input	4CH ,Aviation Plug
	Audio Output	1CH,Aviation Plug
	Compression	G.726 compression, 8KB/s speed
Alarm Input		4Ch Alarm Input, kinds of alarm linkage support
Alarm Output		1CH Alarm Output
Communication interface		1CH RS232 or 1CH RS485 for optional
Position		Support Built GPS/BD Module, built in G-sensor, can repaly and analyse vehicl e driven route.
wireless transmission		Suppport Built-in 3G/4G wireless transmission function, WCDMA, CDMA2000, TDD-LTE, FDD-LTE....
Motion Detection		**Support motion detection alarm. (Can set the video recording duration time after alarm on platform.)**
G-Sensor		Support G-sensor
Storage	SD	Dual SD Card,each max 128GB SD Card loop recording
	Upgrade	Support SD Card remote updating

	File Format	.264
	File System	Special FAT32 File System
Video Playback	Video Search	Search By Record Time/Record Type etc
	Playback	Max support 4CH Replay /Stop/Fast/Slow at same time
		Support forward and backward play at the speed of: x 2,x4,x8,x16.
Voltage & Power	Power Management	Wide Voltage.Support Timed/Delay off
	Voltage Input	DC:+8V ~ +36V
	Voltage Output	+12V@2.5A，+5V@2.5A
	Power Consumption	Normal Working ＜14W , Stand-by status < 0.5W
Working Environment	Temperature	-20℃ to +70℃
	Humidity	20% to 80%
Security	Password	User/Admin 2 Level Different Password
others	Size	112(W) x36(H) x138(D) mm
	Net Weight	360g

عرض المنتج:

查询
查询>>
系统设置
录像设置
网络设置
报警设置
外设设置
系统工具
系统信息
录像搜索
图片搜索
日志查询
调度信息
通话记录


Search
Search >>
Sys Setup
Rec Setup
Network
Alarm
Peripheral
Tools
System
Record
Picture
Log
Dispatch
Call

Product Introduction

Device Series



Product Advantage



العميل واجهة الرسم البياني المستخدم

Appliacation

FUNCTIONS

- Video& Audio real-time monitoring
- Online Vehicle Status
- Satellite Map
- GPS
- Video Storage
- Tracking Display
- Intercom
- Fuel Sensor
- G-Sensor
- Temperature-Sensor

شهادة

VERIFICATION OF CONFORMITY
Verification of Conformity

VERIFICATION OF CONFORMITY
Verification of Conformity

CERTIFICATE OF CONFORMITY
CERTIFICATE
of Conformity

CERTIFICATE OF CONFORMITY
CERTIFICATE
of Conformity

CERTIFICATE OF CONFORMITY
CERTIFICATE
of Conformity
RoHS

CERTIFICATE OF CONFORMITY
CERTIFICATE
of Conformity
RoHS

شركة ومصنع

معرض:

Richmor

CPSE2012 in Shenzhen

CPSE2013

10.29-10.31

4 Booth we have

Welcome you !!!

CPSE2012-- Guangdong TV Report-Shenzhen Richmor

مرحبا بكم في الاتصال سوزي لمزيد من التفاصيل
Wechat: Jobs2lovers،بواسطة البريد الإلكتروني / ويشات
بواسطة سكايب: rcmcctvsales4
بواسطة تراديماناغر: cn1001765398
(بواسطة الهاتف المحمول / ال واتساب: + 86-181 2626 3832 (سوزي زو
بواسطة ق:2355778106