

Richmor 3 **MDR300** **GPS** **WIFI** **SD** **MINI HD DVR**

MDR300

- H.264 . 4 1 . 10 -bit .
- .
- : -
- DVR .
- G (. -
- G (EVDO HSPA HSDPA) .
- .
- UPS DVR 15 10 .
- 100 : -F / (PAL). 120F / (NTSC). : CIF / 2CIF / D1 .
- 2 CH D1 + 2CH CIF.
- 1 G.726.
- 4 2 / channels .
- RS232 RJ45 10M / 100M .
- : -
- ASF. VLC .
- 4 1 .





300 30000 30000

30000 30000 NO	30000
RCM-MDR300D / 301D	30000 30000 30000000
RCM 3000000 3000000	GPS 300000 + 300000 G-300000000
3000000000DG / 301DG	
RCM 3000000 3000000	3 300000 300000G 3000000 GPS 3000000 G-
3000000000SDG /	3000000000
301SDG	
RCM 3000000 3000000	3 300000 300000G 3000000 GPS 3000 3000
3000000000WDG /	3000000 G-30000 3000000 30000000
301WDG	

3000000

3000000 / 30000000	Hisilicon Hi3512 H.264 main profile Linux(2.6)
3000000	3000000 3000000000 30000000 30000000 30000000 3000000 30000000 3000000 30000000 3000000 3000000 & nbsp30000000000 0 0
3000000 3000000 & 300000000 3000000 / 300000000	
/ 30000000 3000000 3000000 300000000	Input: 4 CVBS, 1.0Vp-p, 75Ω; Output: 1 CVBS, 1.0Vp-p, 75Ω
3000000 3000000 3000000 3000000 3000000	3000000 3000000 ISO14496-10
30000 3000000 30000	1 & 3000 3000000 30000 30000000 30000 3000000 & 4 3000000 & 3000 30000000 30000 3000000
/ 30000000 3000000 3000000 300000000	30000 3000000 & 1 30000000 :3000000 3000000 & 30000000 3000000 3000000 & 4 3000000 & :30000000000
3000000 30000000 3000000	3000000000 300000000 3000 30000000 3000000
3000 30000000 3000000	G.726 5 3000000 & 30000000KB / 0
/ 300000000 30000000 3000000 300000000	6 300000000 30000000 30000 3000000 & 1 30000000000 30000000 300000000 30000000
3000000 30000000 3000000	

攝錄影畫質	D1 / HD1 / CIF 畫質 MAX: 2 & 畫質可選 1 或 2 CIF
錄影畫質	1-4 levels, 1 is the highest level and 4 is the lowest level.
錄影模式	Default: Auto Record. Other modes: Timed and Alarm Record (Optional)
錄影儲存	Maximum support one 32GB SD card and one 2.5 inch hard disk.
錄影搜尋	Search Video Record according to record time, record mode and record storage device etc.
錄影時間	錄影時間可選 1 或 2 小時 & 4 小時錄影時間可選。
通訊	
遠端控制	RS232 interface for remote control; RJ45 10M/100M Ethernet port.
通訊	Built-in 3G (WEVDO,CDMA200,TD-SCDMA) or optional GPRS,WIFI and EDGE
GPS	GPS 定位 & G-PRS 定位
工作溫度 / 儲存溫度	工作溫度 ~ °C25- 儲存溫度 & : °C50+ 工作溫度 ~ °C0 儲存溫度 & : °C50+

攝錄影畫質



AV Cables



Power Cables



IO Cables



Remote Control



WIFI Antenna



3G Antenna



GPS Antenna



CD (Manual & Software Inside)

□□□□ □□ □□□□□□ □□□□□□□□ □□□□□□



CE FCC ROHS □□□□



□□□□



Richmor Brand Package



Standard Package

□□ □□□□ □□□□ □□ □□□□!

□□□□□□□□ □□ □□□□ □□□□ □□□□□□□□ □□ □□□ □□□□□:

□□□□□□□□□□ □□□□□□: jenny@rcmccctv.com

□□□□□□: rcmccctvsales4