x	
× 0000 WIN8 00, 0000000	
h. 264 compression,4ch [] 720 p/1080 p [] [] [] []	
CH [][][] (1CH cvbs []], 1CH vga [][][][]	
10000000000, DO sd DOO, DOODOOOO	
3-36V [][], [][][]	
□□□ ups □□, □□□□□□□□□, □□□□□□8-10□	
n + sd nn (nn2.5 nn, nn 128G sd n) nnnn & nnn; nn usb nnnnnnn;	
0 2 usb 00000000000000000000000000000000000	
008CH 0000 (1CH 00 + 7CH io 0000), 2CH 000000	
]□ 1 ch can □□□	
□ gps/bd/g □□□□□□;	
1030/4 g 000000;	
]_ wifi,	
] sms;	
ota (000) 0000000, 00000000, 000000	

_____nvr—mnvr9204

00000, h. 264 00, 0000, 00 4CH 1080P 0000000;
$thm:linear_conding_1080P/720 p/cif/HD1/d1 pdf_recording_1080P/720 p/cif/HD1/d1 pdf_recording_recor$
00000 Design,8-36V 000, 000000/00/0000, 00000000;
0012VDC 0000, 000/00000; 00 + sd 000 (00 2.5 "00 + 00 128GB sd 0", 00 nvr 0000 & 0000; 00000000, 00 sd 0000;
0000 dvr 0000000, 0000000000, 00000000
acc [][], [][]24[];
000 ups 00, 000000000, 00000010-15s0
0000/0000/00000000, 00000000; 00000/00/0000/0000, 0000; 00 GPS/BD,3G/4G 000, wifi 00; 00000, 000000, 000000000000; 00000000000 & 00000000000; 7CH 0000 (000000000000), 0000000;
2CH 0000, 00000000, 0000/0000
1CH can [], [][][][]
0000000, 0000, 00000, 000; 00000 gui 00, 00000000000000000; 0000 sd 0 ota 000000, 00000;

		linux
		h. 264 [][]
osd		0000, 0000000 id
gui		
		4CH 1080p [], [][][]
		1CH cvbs + vga □□□□, 1.0Vp-p, 75
		1080 p/720 p/d1/HD1/cif, MAX:4 □□1080p
		0-7 _, 0, 7
		cif: 256Kbps ~ 1.5Mbps, []]]]]]]]
		HD1: 600Kbps [] 2.5Mbps, [][][][][]
		D1: 800Kbps [] 3Mbps, [][][][][][][][]
		720 p: 4 mbps-6 mbps, [][][][][][][][][][][][][][][][][][][]
		4CH
		1CH
		g. 711 [], 8 kb/[]]
	ļUU	8CH io [][][][][][][][][][][][][][][][][][][]
		2CH 000/00000, 00000000, 0000/000
		2CH RS232,, posled 2CH 485, ptz
		2CH 465 □□, □□□ ptz □□ 1CH can □□□
		□□□□3□/4 g □□, WCDMA,CDMA2000,TDD-LTE,FDD-LTE□
		$[\Box\Box\Box\Box\Box\Box]/4\ g\ \Box\Box$, WCDMA,CDMA2000,TDD-ETE,FDD-ETE \Box
g 🗆 🗆		
		2.5 " + sd _,2TB + 128GB sd,
		O usb OOOO, sd OOO, ota OOOOO
		. 264
	usb	0000 usb 00, 00 usb 0000000;000 usb 00, 000000
		DC:+8V ∏ + 36 v
		+ 12V@2.5A + 5v@2.5a
		ups 00, 000000000000000000000000000000000
		□□□ 5 w
		-20°C∏70°C
		20%
	Inn	40 /0 00 /0

	187 (d) * 188 (w) * 67 (h) mm
	1.8kg