

Richmor

RCM-LPC218

RCM-LPC218

all-metal internal structure, impact, corrosion, protection grade IP66

Low power consumption, easy to heat, long life, radiation distance

300m

Horizontal operation monitoring range far and wide range of vertical operation monitoring

360 ° 180 ° °

Built-in decoder, integrated multi-protocol, multi-brand cameras baud rate and protocol;

Support OSD menu function, POST display dome current information, 60 seconds of self-learning function;

The exact angle of 0.1 degrees always shows the exact function of the angle moves;

128;

Built-in surge and lightning protection devices and data memory function

RCM-LPC216-18 RCM-LPC216-26 RCM-LPC216-36

RCM-LPC216-18 RCM-LPC216-26 RCM-LPC216-36

1/4" HAD CCD

752H × 582V

/

VBS 1.0Vp-p/75

/

480TVL

≥ 50

1/1 1/10 000 1/3 1/10 000

0.01LUX

Focal Length F = 3.4 ~ 122.4mm 36x f = 3.5 ~ 91.0mm 26x f = 4.1 ~ 73.8mm 18x

/

0.1 ° 100 ° /

0.1 ° 60 ° /

360 °

-90 ° + 90

128

RS485

90

□□□□-30 ° C□55 ° Ç

□□□□60VA

□□AC24V

