

## Main Features

- New His solution, H.265 compression mode,
- Integrate DSM driving behavior and driver face recognition function;
- 4CH MDVR, built-in one AHD camera, and support 3CH external.
- New flat interface, support remote control or Mouse via LCD screen, and Mobile Phone APP Configuration directly.
- Support mobile Phone APP preview maintenance, real-time preview function of mobile terminal
- Easy to install with 3M directly, save 1/10 installation time comparing to normal MDVR
- Integrated front camera can be adjusted in the vertical direction, and the camera could be completely locked through the structure after adjustment
- Integrated vehicle Microphone, and Speaker, convenient to two-way talk.
- Four status Led indicators to show device working status
- Support WiFi and Wifi hotspot (share 6ID max)
- Built-in GPS/BD modules to achieve speed, position, time and route management
- Support line departure and area entry and exit alarm, device max can save 16 lines and areas
- Support driving line departure and area in and out alarms, the device can save up to 16 lines and areas
- Support dual TF cards (max 256G each)
- 5CH alarm input, 1CH of alarm output, support photo capturing manually
- 1CH USB , 2CH RS232 and 1CH RS485
- Supports low temperature startup and work. The machine has a highly reliable heat dissipation design, and the working temperature can reach: -40°C to 70°C.

