

Richmor



SMS Device configure
OTA Remote Updating
5CHANNEL 1080P+720P HD
2TB HDD + 128GB SD





SMS Device configure
OTA Remote Updating
5CHANNEL 1080P+720P HD
2TB HDD + 128GB SD

Richmor





welcome to log in, rntest | religin | Video | Map | playback | System Set | Log Query

Dev List | Polling | My Map

Monitor Center(3/12)

- 80027
- 80029
- 贵C82868
- 80002
- 80004
- 80035
- 99038
- TH51
- 基8Y8156
- 湘80023
- 贵C87626
- 贵C87628

Status	PTZ	Color	VOIP
DeviceType	MDVR		
Vehicle Name	贵C82868		
Vehicle ID	99057		
Company			
Their group	Monitor Center		
Status	Online		
Positioning Time	2014-12-19 11:16:24		
Vehicle Location	贵州省遵义市桐梓县崇遵高速公路		
Speed	82.40 km/h(North)		
Costs	Normal		

Monitor:12 Online:3 Alarm:0 Offline:9 Idling:0 ACC OFF:0 GPS Invalid:1 Export Auto Sort

Device	Positioning Time	Position	Speed	Alarm
80002	2014-12-10 18:33:08	四川省宜宾市兴文县香山西路59号	1.70 km/h(North)	
贵C87626	2014-12-19 10:48:39	贵州省遵义市桐梓县崇遵高速公路	7.70 km/h(West)	
贵C82868	2014-12-19 11:16:24	贵州省遵义市桐梓县崇遵高速公路	82.40 km/h(North)	
贵C87628	2014-12-17 10:58:58	贵州省遵义市桐梓县崇遵高速公路	0.00 km/h(North)	

Running: 00:02:05 Number of device: 12 Online: 3 / number of set loss: 6 / Areas: 0 / Total: 12 line rate: 25.00% / Lost rate: 50.00%



GPS Positioning & Overspeed Alarm

GPS data including Latitude, Longitude, and speed of vehicles will be saved along with video footages on to the SD card or hard disk, while playing the footages you can also check the the locations of your vehicles on map. Besides, alerts would be triggered while driving overspeed.



2TB + 128GB Large Capacity Storage

Up to 2TB hard disk & 128GB SD Card supported at the same time for saving video footages, once the disk is full, the DVR will overwrite the earlier files to make space for new files, which means you can have the DVR recording all the time to look after your vehicle.

Alarm I/O Alarm & Alarm Recording

The DVR supports 6 I/O inputs and 1 alarm output. You can set those Inputs to record vehicle bracking, turning left/ right, door opening and more. Also, they can be simply used as a Panic Button, or work with other external sensors to trigger recording or send message to the monitor center.



5CH 720P HD + 1080P HDD

MDVR

* HIS H.264 5ch Million Pixels 4CH 720p + 1CH 1080P

* 3CH 2CH CVBS; 1CH VGA

* DVR

* 6-36V / 10Amps 12V & 5V

* UPS 8-10s

*□□+ SD□□□□□□2.5"□□□□□□128G SD□□□□□□;□□USB□□□□□□□□□□□□;

*\$2 USD

$$*9\text{CH}_2 + 8\text{CH}_2\text{IO} + 2\text{CH}_2$$

*HDD

*GPS / BD / G-Sensor

*3G / 4G

*□□□□/□□/□□□□□;□□□□□□□□/□□□□□□/ POS / LED□□□□;

*OTG

*iOS / Android

*

11

OS	Linux
OS	DD/MM/YY
Codec	H.264
OSD	XXXXXXXXXXXXID
GUI	XXXXXXXXXXXX
	4CH 720P+ 1CH 1080P1.0Vp-p75Ω
	2CH CVBS+ 1CH VGA1.0Vp-p75Ω1CH4CH
	145/
	1080P / 720P / D1 / HD1 / CIFMAX4720P + 1080P / 4D1
	1-41
	PAL100f / sCCIR62550field;
	NTSC120f / sCCIR52560field;
	CIF256Kbps1.5Mbps8;
	HD1600Kbps2.5Mbps8;
	D1800Kbps3Mbps8;
	720P4Mbps-6Mbps
	XXXXXXXXXXXX
	4CH
	2CHBNC
	G.7268KB / s
	7CH1CH ADXXXXXXXXXXXX
	2CH/
	3CH RS232POS / / LED
	2CH 485PTZ

通訊	支援3GPP WCDMA CDMA2000 GPRS EDGE; 支援4GPP TDD-LTE FDD-LTE
GPS	支援GPS / BD
儲存	HDD 2.5"
	SD 128GB SD
	支援USB SD OTA
	H.264
	FAT32
USB	USB U
通道	4CH / /
	x 2 x 4 x 8 x 16
尺寸	2
通訊	TTS
	erial LED POS OBD
	/ / / /
電壓&電流	DC + 6V- + 36V + 12V 1.5A + 5V 1.5A
	<5W
溫度	-20°C - + 70°C
	20-80
Ohters	200D* 187W* 62H mm 1.90Kg





00

00000

HIS0000H.26400000005CH AHD000004CH00720p00000000000000+ 1CH 1080P00000000

000000001080P / 720P / CIF / HD1 / D100000000;

000000006-36V0000000000/00 - - 00/00000000000000;

00 12VDC 0000000000/000000;

002TB00+ 128GB SD0000000000DVR00000&00000;

000000000000SD00000;



GPS

GPS
GPS
GPS
GPS

FQA

GPS
A
1.Net
2.Net
SD
HDD
SD
SD
SD

1. 選擇HDD / SD
 A. 1. 選擇HDD / SD
 2. 選擇HDD / SD
 3. 選擇HDD / SD



Richmor Brand Package



Standard Package



DHL / UPS Etc

2-5

5-10



MoneyGram

PayPal

HSBC



Richmor

CPSE2012 in Shenzhen



CPSE2013

10.29-10.31

4 Booth we have

Welcome you !!!



CPSE2012-- Guangdong TV Report-Shenzhen Richmor



