

## Newest Police Body Worn Camera infrared waterproof portable DVR Packaging & Delivery

Packaging Details:	Color Box/ Carton Box
Delivery Detail:	3~5 work days for sample order



### Main Features

- 1) 2.4 inch Color Display Built-in;
- 2) 2100mAh large Capacity Li-ion Battery;
- 3) Full D1 Real-time Video & Audio Recording;
- 4) Max. 128GB Micro-SD Card Supported;
- 5) Built-in GPS Module.
- 6) 2-way audio, supports PTT talkback;
- 7) 3G/ 4G Remote View on PC or Smartphone;
- 8) Built-in Wi-Fi Module.

### Specifications

Operating System	Linux	
Security Management	Administrator Password	
Video and Preview	Video Input	External Camera, Above 70 degree View Angle
	OSD	Time/ Date/ Device ID/ GPS
	Video Compression	H.264 Compression Coding
	Dual-Stream	Supported
	Resolution	D1/ HD1/ CIF Selectable
Audio	Audio Input	External Microphone
	Audio Compression	G.726 coding
Recording	Storage Medium	Micro-SD card(1G ~ 128G)
	File Format/ System	ASF/FAT32
	Record Mode	Auto Recording after Startup
	Video Searching	Search by Date/ Time
	Playback	Local Playback; Support 2/ 4/ 8/ 16 Times Fast forward/ Backward
TFT Display	Size	2.4 inch LCD
	Resolution	480*234
Wireless Transmission	3G Module Built-in (4G Optional)	
Wi-Fi	built-in WIFI module	

GPS	built-in GPS Module	
System Upgrading	Upgrading from TF Card	
Power Supply	Battery Capacity	Li-ion Battery, 2100mAh, 7.4V
	Charging Time	Less than 3 hours
	Working Hour	Above 4 hours
Operating Environment	Temperature	-20°C~+50°C
	Humidity	20% to 90%
Dimensions	65(W) x130(H) x30(D) mm	
Three Proofings	Grade: IP54	
Weight	Net: 475 g, (1.05LB)	

## Product Showcase





Client Software

# Mobile monitoring and management platform

This screenshot shows the main interface of the mobile monitoring and management platform. It features a top navigation bar with icons for Home, Playback, System Set, Log Query, and External App. The left sidebar contains a 'Dev List' with a tree view of monitoring centers and vehicles, and a detailed view for a selected vehicle.

The main area displays a map with a vehicle location marker. Below the map is a table of vehicle data:

Device	Positioning Time	Position	Speed	Alarm	Status
贵C37762	2015-08-11 10:11:48	福建省福州市仓山区(国家奥体中心)	0.0 km/h(Northward)		OK

At the bottom, a status bar shows system metrics: Running: 02:00:01, Online 5, Number of set loss 0, Alarms 0, Total 12, Live Ratio: 1.67%, Lost Ratio: 0.7%.

# Mobile monitoring and management platform

This screenshot shows the 'System Parameters' configuration screen within the mobile monitoring and management platform. The left sidebar remains the same, but the main area is filled with various configuration options.

Key configuration items include:

- Language: English
- UI Style: Default
- Exit System: Not Close (No Operation Condition)
- Image Capture: On GPS\_ID ONLY (COPY CAPTURE)
- Location: 72 (N/C Indicates variable loss)
- GPS update time: 0 (Unit: s/2-100)
- IO type: (Empty field)
- Enable:
- Default choice of online equipment:
- Enable multi-screen mode:
- Efficient multi display:
- Deploy the vehicle of the city:

A 'Save' button is located at the bottom right of the configuration area. Below the configuration is a table showing vehicle data:

Device	Positioning Time	Position	Speed	Alarm	Status	Message	Other Info
贵C37762	2015-08-11 10:11:53	福建省福州市仓山区(国家奥体中心)	0.0 km/h(Northward)		Online	ACC OK, SC	SD Card Full

The bottom status bar shows: Running: 00:01:15, Online 5, Number of set loss 0, Alarms 0, Total 12, Live Ratio: 41.67%, Lost Ratio: 0.7%.





## Applications



Welcome to contact RICHMOR for more details!

Skype:rcmctvsales5

WhatsApp: +86-18126263838