

## Overview

Super Wide Voltage,Special UPS Tech,High Capacity SD Card,Many Recording Mode for Option,Support 3G GPS,All Aviation Connectors,4CH Video+2CH Audio,CIF and D1 Switched Freely,Security Key for SD Card and SIM Card,Support PTZ Controland Mobile Phone Remote Monitoring.



Item	Parameter
A&V Input	4 channel, aviation connector
A&V Output	1 channel, aviation connector
Video compression format	H.264
Resolution	D1/HD1/CIF selectable. D1-the highest, CIF-the lowest

Video Frame rate	100 fps (PAL),120fps(NTSC),50fps(4*D1)
Recording	Fire recording, time recording, alarm recording
Storage	SD card
Alarm	1CH alarm; alarm and recording at the same time
Vehicle recording	Recording Vehicle operation (turn left/right, stop lamp), license NO. ,route, driver
System Protection	Saving the recording data when the power off, support hard disk upgrading
Network	RJ45 Ethernet interface and can copy the data through Wired/Wireless networks, controlling and managing the main machine.
PTZ control	RS232 can turn to PTZ interface
GPS	Support GPS module expansion, recoding and playback the vehicle route
G-SENSOR module	Support G-Sensor module expansion, recording vehicle direction state and alarm
Battery	Wide Voltage Range. Operation voltage: 6V~48V; Recommend range: 8V-40V; instantaneous range: 6-70V. Support overvoltage protection, under-voltage protection, short-circuit protection, transposition protection, fire on/off timing,delay power-off. Output voltage is 12v .
Powder	2.4W
System	Embedded full-time multitask control system, support Chinese simplified & English
Working environment	Working temperature: -20C°to 50C°,Working humidity: <90%; storage temperature: -30C to 70C,Storage humidity<90%
Dimensions	180mm*145mm*45mm

## Package



Richmor Brand Package



Standard Package

Own Designed Software Screenshot

