

product specifications

| Item | parameter | |
|---------------------------|-----------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating System | Linux | |
| Language | English/chinese/customized | |
| Video Compression | H.264 Compression | |
| OSD | overlays information such as date time and vehicle ID | |
| GUI | Graphical user interface setup system parameters with the remote control | |
| Video Record System | video input | 4CH 960P/720P AHD input,aviation connector, 1.0Vp-p, 75Ω |
| | video output | 1 CVBS, 1.0Vp-p, 75Ω,Aviation,Support 1CH Full Screen,4CH Screen view |
| | preview | Support 1 channel and 4 channels preview., Support Manual/Alarm Trigger full screen preview |
| | resolution | 720P/D1/HD1/CIF, MAX:4 channels of 720P and 4 channels of D1 |
| | image quality | 1-4 levels, 1 is the highest level. |
| video standard | video standard | PAL: 100f/s , CCIR625 line,50field; NTSC: 120f/s, CCIR525 line,60field; CIF: 256Kbps ~ 1.5Mbps, 8 level video quality optional; HD1: 600Kbps ~ 2.5Mbps, 8 level video quality optional; D1: 800Kbps ~ 3Mbps, 8 level video quality optional; 720P: 4Mbps-6Mbps, multi level video quality optional |
| | record mode | The default setting is auto recording after power on. Timed recording, alarm trigger recording and manual recording are supported. |
| Audio | audio input | 4CH Aviation Plug Input |
| | audio output | 2CH,headphone connect at front panel, BNC Connect on Back panel |
| | compression | G.726 compression, 8KB/s speed |
| Alarm Input | 7CH Alarm Input,1CH AD Input,impulse speed input,Alarm Linkage | |
| Alarm Output | 2CH Alarm Output,Support Light/Sound alarm sensor,Oil/Power cut off | |
| Interface | | 3CH RS232, POS/Fuel Sensor/LED Advertisement Connection |
| | | 1CH 485 Interface,Connect PTZ Camera |

product show



SMS Device configure
OTA Remote Updating
8CH Full D1 Real time monitor
2TB HDD + 128GB SD Card

Richmor

OEM/ODM Customized
Factory Price
Independent R&D Tech
Low Moq





- SMS Device configure**
- OTA Remote Updating**
- 8CH Full D1 Real time monitor**
- 2TB HDD + 128GB SD Card**

Richmor

- OEM/ODM Customized
- Factory Price
- Independent R&D Tech
- Low Moq



System Structure

Richmor



Richmor

OEM & ODM Service

Brasil World Cup Supplier
www.rcmctv.com



Truck
Coach



School Bus
Bus



Police Car
Taxi



Support
All Vehicles