

Richmor HD H.264 3G GPS-Fahrzeug-Recorder DVR MDR500SDG

- 1, Latest New H.264 Video Compression, G.726 Audio Code, 4CH Video & 2CH Audio.
- 2, Recording Mode Can be Option CIF/HD1/D1, Frame Quality Can be Adjusted.
- 3, Professional Power Design for Vehicle, 6~48V Wide Voltage; Over-load, Over-voltage, Short Circuit, Reverse Protection.
- 4, All Aviation Connectors, Super Stable, High Anti-shock, Easy installation plug in and out.
- 5, Support DC12V, DC5V Output, Can offer Power for Cameras and some Accessories.
- 6, 64GB SD Card Max with Data Redundary Tech, Ensuring Data Stable.
- 7, Auto Recording, Timing Recording, Alarm (Open/Close door) Recording Mode for Different Request.
- 8, Powerful file fragmentation removal technology and data protection features, support for abnormal restart protection function.
- 9, Special Delay Power off circuit, Which can support the system continuous running after vehicle power off.
- 10, 4CH & Alarm & Eingangssteuerung, Local & und & Fern & PTZ & Kontrolle.
- 11, Support 3G, GPS, 3G Module: WCDMA/CDMA2000/TD-SCDMA..., Compatible with GPRS/EDGE;
- 12, Free software offered, Support Real-time Live video, GPS Location, Screenshot, Playback, Analysis, Alarm, Log Management.
- 13, Support Upgrading through SD Card; support phone monitoring Android/iOS.



Beschreibung

Artikel	Parameter
A & amp; V & nbsp; Eingang	4 & nbsp; Kanal, & nbsp; Luftfahrt & nbsp; & nbsp; & nbsp; Stecker
A & amp; V & nbsp; Ausgang	1 & nbsp; Kanal, & nbsp; Luftfahrt & nbsp; & nbsp; & nbsp; Stecker
Video & nbsp; Kompression & nbsp; Format	H.264
Auflösung	D1 / HD1 / CIF & nbsp; wählbar. D1-& nbsp; höchste, & nbsp; CIF-& nbsp; niedrigsten
Video & nbsp; Frame & nbsp; Rate	100 & nbsp; fps & nbsp; (PAL), 120fps (NTSC), 50fps (4 * D1)
Aufnahme	Fire & nbsp; Aufnahme, & nbsp; Zeit & nbsp; Aufnahme, & nbsp; Alarm & nbsp; Aufnahme
Lagerung	SD & nbsp; Karte
Alarm	1CH & nbsp; Alarm; & nbsp; Alarm & nbsp; und & nbsp; Aufnahme & nbsp; AT & nbsp; dem & nbsp; gleiche & nbsp; Zeit
Fahrzeug & nbsp; Aufnahme	Recording Vehicle operation (turn left/right, stop lamp), license NO., route, driver
Nbsp System & Schutz	Saving the recording data when the power off, support hard disk upgrading
Netzwerk	RJ45 Ethernet interface and can copy the data through Wired/Wireless networks, controlling and managing the main machine.
PTZ & nbsp; Steuer	RS232 & nbsp; kann- & nbsp; drehen & nbsp; & nbsp; PTZ & nbsp; Schnittstelle
GPS	Support GPS module expansion, recoding and playback the vehicle route
G-Sensor & nbsp; & nbsp; & nbsp; Modul	Support G-Sensor module expansion, recording vehicle direction state and alarm
Batterie	Wide Voltage Range. Operation voltage: 6V~48V; Recommend range: 8V-40V; instantaneous range: 6-70V. Support overvoltage protection, under-voltage protection, short-circuit protection, transposition protection, fire on/off timing,delay power-off. Output voltage is 12v .
Pulver System	2.4W Embedded full-time multitask control system, support Chinese simplified & English
Arbeiten & nbsp; Umwelt	Working temperature: -20C°to 50C°.Working humidity: <90%; storage temperature: -30C to 70C.Storage humidity<90%
Größe	180mm * 145mm * 45mm

Zubehör



AV Input Cables



AV Output Cable



Power Cable



IO Cables



Remote Control



GPS Antenna



CD (Manual & Software Inside)



SD Mobile DVR

Paket



Richmor Brand Package



Standard Package

Eigene & Design & Software & Screenshot



CE & FCC & ROHS & Zertifizierung



Willkommen & nbsp; & nbsp; Kontakt & nbsp; Jenny & nbsp; für & nbsp; Details

E-Mail: jenny@rcmctv.com

Skype: [rcmctvsales4](https://www.skype.com/en/contacts/voice/rcmctvsales4)