

Richmor HD H.264 3G GPS del vehículo DVR Grabador MDR500SDG

- 1, Latest New H.264 Video Compression, G.726 Audio Code, 4CH Video & 2CH Audio.
- 2, Recording Mode Can be Option CIF/HD1/D1, Frame Quality Can be Adjusted.
- 3, Professional Power Design for Vehicle, 6~48V Wide Voltage; Over-load, Over-voltage, Short Circuit, Reverse Protection.
- 4, All Aviation Connectors, Super Stable, High Anti-shock, Easy installation plug in and out.
- 5, Support DC12V, DC5V Output, Can offer Power for Cameras and some Accessories.
- 6, 64GB SD Card Max with Data Redundary Tech, Ensuring Data Stable.
- 7, Auto Recording, Timing Recording, Alarm (Open/Close door) Recording Mode for Different Request.
- 8, Powerful file fragmentation removal technology and data protection features, support for abnormal restart protection function.
- 9, Special Delay Power off circuit, Which can support the system continuous running after vehicle power off.
- 10, 4CH Alarm Input, Local PTZ y remote de control.
- 11, Support 3G, GPS, 3G Module: WCDMA/CDMA2000/TD-SCDMA..., Compatible with GPRS/EDGE;
- 12, Free software offered, Support Real-time Live video, GPS Location, Screenshot, Playback, Analysis, Alarm, Log Management.
- 13, Support Upgrading through SD Card; support phone monitoring Android/iOS.



Descripción

Artículo	Parámetro
A & amp; V & nbsp; de entrada	4 & nbsp; canal, & nbsp; la aviación & nbsp; & nbsp; & nbsp; conector
A & amp; V & nbsp; salida	1 & nbsp; canal, & nbsp; la aviación & nbsp; & nbsp; & nbsp; conector
Video & nbsp; compresión & nbsp; formato	H.264
Resolución	D1 / HD1 / CIF & nbsp; seleccionable. D1-el & nbsp; más alto, & nbsp; CIF-el & nbsp; más bajo
Video & nbsp; Frame & nbsp; tasa Grabación	100 & nbsp; fps & nbsp; (PAL), 120 fps (NTSC), 50fps (4 * D1)
Almacenamiento	Fire & nbsp; grabación, & nbsp; time & nbsp; grabación, & nbsp; alarma & nbsp; grabación SD & nbsp; tarjeta
Alarma	1 canal de & nbsp; alarma; & nbsp; alarma & nbsp; y & nbsp; grabación & nbsp; at & nbsp; & nbsp; misma & nbsp; tiempo
Vehículos & nbsp; grabación	Recording Vehicle operation (turn left/right, stop lamp), license NO., route, driver
System & nbsp; Protección	Saving the recording data when the power off, support hard disk upgrading
Red	RJ45 Ethernet interface and can copy the data through Wired/Wireless networks, controlling and managing the main machine.
PTZ & nbsp; de control	RS232 & nbsp; se & nbsp; girar & nbsp; & nbsp; PTZ & nbsp; interfaz
GPS	Support GPS module expansion, recoding and playback the vehicle route
G-SENSOR & nbsp; & nbsp; módulo	Support G-Sensor module expansion, recording vehicle direction state and alarm
Batería	Wide Voltage Range. Operation voltage: 6V~48V; Recommend range: 8V-40V; instantaneous range: 6-70V. Support overvoltage protection, under-voltage protection, short-circuit protection, transposition protection, fire on/off timing, delay power-off. Output voltage is 12v.
Poivo	2.4W
Sistema	Embedded full-time multitask control system, support Chinese simplified & English
Trabajo & nbsp; medio ambiente	Working temperature: -20C°to 50C°, Working humidity: <90%; storage temperature: -30C to 70C, Storage humidity <90%
Dimensiones	180mm * 145mm * 45mm

Accesorios



AV Input Cables



AV Output Cable



Power Cable



IO Cables



Remote Control



GPS Antenna



CD (Manual & Software Inside)



SD Mobile DVR

Paquete



Richmor Brand Package



Standard Package

Propios & nbsp; Diseño & nbsp; Software & nbsp; Captura de pantalla



CE & nbsp; FCC & nbsp; ROHS & nbsp; Certificación



Bienvenido & nbsp; & nbsp; Contacto & nbsp; Jenny & nbsp; de & nbsp; detalles

E-mail: jenny@rcmctv.com & nbsp; & nbsp; & nbsp; & nbsp; & nbsp; & nbsp;
Skype: [rcmctvsales4](https://www.skype.com/en/contacts/voice/rcmctvsales4)