product specification:

product spec Item		parameter
Operating System		Linux
Language		English/chinese/customized
Video Compression		H.264 Compression
OSD		overlays information such as date time and vehicle ID
GUI	Graphical user interface	setup system parameters with the remote control
Video Record System	video input	4CH 960P/720P AHD input, aviation connector, 1.0Vp-p, 75Ω
	video output	1 CVBS, 1.0Vp-p, 75Ω, Aviation, Support 1CH Full Screen, 4CH Screen view
	preview	Support 1 channel and 4 channels preview., Support Manual/Alarm Trigger full screen preview
	resolution	720P/D1/HD1/CIF, MAX:4 channels of 720P and 4 channels of D1
	image quality	1-4 levels, 1 is the highest level.
	video standard	 PAL: 100f/s , CCIR625 line,50field; NTSC: 120f/s, CCIR525 line,60field; CIF: 256Kbps ~ 1.5Mbps, 8 level video quality optional; HD1: 600Kbps ~ 2.5Mbps, 8 level video quality optional; D1: 800Kbps ~ 3Mbps, 8 level video quality optional; 720P: 4Mbps-6Mbps, multi level video quality optional
	record mode	The default setting is auto recording after power on. Timed recording, alarm trigger recording and manual recording are supported.
Audio	audio input	4CH Aviation Plug Input
	audio output	2CH,headphone connect at front panel, BNC Connect on Back panel
	compression	G.726 compression, 8KB/s speed
Alarm Input		7CH Alarm Input,1CH AD Input,impulse speed input,Alarm Linkage
Alarm Output		2CH Alarm Output, Support Light/Sound alarm sensor, Oil/Power cut of
Interface		3CH RS232, POS/Fuel Sensor/LED Advertisement Connection
		1CH 485 Interface, Connect PTZ Camera
Wireless Transmission		Support Built in 3G transmission,, WCDMA, CDMA2000,GPRS, EDGE; Built in 4G module optional, TDD-LTE, FDD-LTE
GPS Position		Support Built GPS/BD Module
	HDD	Max 2.5" 1TB HDD
Storage	SD Card	Max 128GB SD Card Mirror Recording Keep Data Safety
	update	Support USB Updating, SD Card Updating, OTA Remote Updating
	file format	H.264
	file system	Special FAT32 File System
	USB	USB Interface on Front Panel for data back up by U Disk,Hard Disk
	video search	Search By Record Time/Record Type etc
Record Replay	playback	Max support 4CH Replay /Stop/Fast/Slow at same time
	playback	Support forward and backward play at the speed of: x 2,x4,x8,x16.
Secu	-	User/Admin 2 Level Different Password
Optional Functions	voice call	Support voice call each other
	TTS Voice broadcast	Support TTS voice broadcast function.
	serial expand	Support LED Advertisement Panel, Oil Sensor, POS, Bus Station Broadcaster, Car OBD, ect. external device
	Power Management	Wide Voltage.Support Timed/Delay off
Voltage & Powe	Input Voltage	DC:+6V - +36V
	Output Voltage	+12V~1.5A,+5V~1.5A
	Power	Working<5W
Working	Temperature	-20°C - +70°C
Environment	Humidity	20% - 80%

Othors	Size	200 (D)* 187(W)* 62(H) mm
Others	Weight	1.90Kg

Product Show;





Client User Graph Interface





Appliacation

FUNCTIONS

- Video& Audio real-time monitoring
- Online Vehicle Status
- Satellite Map
- GPS
- Video Storage
- Tracking Display
- Intercom
- Fuel Sensor
- G-Sensor
- Temperature-Sensor



certificate



company and factory






Richmor OEM & ODM Service Brasil World Cup Supplier



Exhibition:

Richmor

CPSE2012 in Shenzhen



Welcome you !!!



CPSE2012-- Guangdong TV Report-Shenzhen Richmor



Welcome to contact Susie for more details

- By Email/wechat,Wechat:Jobs2lovers
- By Skype:rcmcctvsales4
- By Trademanager:cn1001765398
- By Mobile phone/Whatsapp:+86-18126263832(Susie Zhou)