

XXXXXXXXXXXXXXXXXXXXXXXXXXXX

RCM-SP5800

XXXX

XXXXXXXX1XXXXXXXXDVR

2XXXXXXXX LAN3GGPS

3XXXX XXXXXXX

4XXXXXXXXXXXXSDXXXX

5XXXXXXXXXXXXSDXXXXXXXXXXXX

XXXXXXXX6recovery

XXX





参数

名称	规格	备注
基本参数	型号	HT-8000
	尺寸	125mm x 65mm x 25mm
	重量	约 150g
	工作温度	-20℃ ~ 60℃
摄像头	镜头	70° CMOS
	OSD	支持 OSD 菜单
	分辨率	264K Hisilicon
	帧率	支持 VGA/QVGA
	码率	QVGA 400kbps ~ 1.5Mbps
	帧大小	VGA 1000kbps ~ 2Mbps
	接口	支持 USB
	其他	支持
功耗	待机	约 10h
	通话	约 1h
	发射功率	> 1W
其他	符合 G.726	

SD	Capacity	1GB / 32GB
	File System	ASF / FAT32
	Resolution	1080P
	Frame Rate	30FPS
USB	Port	USB 2.0
	Speed	3G WCDMA / CDMA2000 / TD-SCDMA / GSM / GPRS / EDGE
Display	Screen	2.4" TFT
	Resolution	480 * 234
	Storage	SD Card
Temperature	Operating	-20°C ~ +50°C
	Storage	20" * 80"
Dimensions	Width	50mm * 90mm * 28mm
	Height	70mm * 110mm * 28mm
Weight	Net Weight	95g
	Gross Weight	307.5g
Power	Input	238V
	Output	352V

**CMS**

**Vehicle with device for test in AC Coach  
Lahore to Sadiq Abad near motorway @ 86Km/h**

Windows PC

IOS & Android OS



□□□□□□□□□□DVR□□□□□□□□















Inner Training after study from Alibaba in July



Technical Training For Fast Response to Customer Richmor 锐驰曼



lecturer for Execution