

P2P

- 1. RMON iOS Android
- 2. USB SD
- 3.
- 4.
- 5. 3D
- 6.

P2P





phone



pad



pad



NPC



NPC



NPC



P2P

处理器	Hi3512
操作系统	Linux
图像传感器	CMOS 30W
分辨率	264
制式	PAL / NTSC
屏幕	VGA 640×480
帧率	VGA @ 25 FPS 30 FPS
镜头	0.1LUX / F1.2
接口	BT656 / 3.5" TFT
认证	G.711A
存储	USB / SD

□□□□□
□□□□□□□
□□□□□□□□□□□□

USB

TF

WIFI

□□□□□□

□□□□

PTZ□□□□□□

□□□

□□□□

□□

□□□mm□

□□

□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□

RJ45&NBSP□□&NBSP□□100M&NBSP□□/&NBSP□□1000M&NBSP□□100BASE-TX

1 *&NBSP□□USB□□□&NBSP□□2.0

1 * TF

□□□□□□802.11&NBSP□□b / g□/ n□

3.5□□□□□□□□□□

DC&NBSP□□12V&NBSP□□□2□a□

□□□□□□□□□□

2W

0°C - + 55°C

10□-90□

109 * 117 * 213□mm□□

800□□□

Remote monitoring
(IOS and Android)

Local monitoring
(Rec By USB, micro sd)

Alarm Sent E-mail
(Speaker, Rec, E-mail)

Video Phone
(by dial-up no Correspondence)

I'm

23CM

0.8Kg

P2P□□□□□□□□□□□□



Richmor

- 1 3
- 2
- 3 CE FCC RoHS