



Easily Smart GUI Interface, saving time in device setting.

Main Features

HIS Solution,H.264 Compression,multiple stream recording,support 5CH video input, video recording and playback (4CH real-

time 720p million pixels Analog HD input /4CH analog standard definition input/2CH analog input+2 CH HD mixed input + 1CH 1080P network camera input);

3CH video output (2CH CVBS video output, Support front and rear output; 1CH VGA output for optional)

Exclusive pre-

allocate DVR Special File System Technology, Solving repeatedly wipe cause file fragmentation, solving storage file system crash, data loss and cannot find storage media and file garbled, ensure the in tegrity of the data.

8-36V wide voltage with low power consumption. Support Reverse Protection□over-voltage/over-current protection.Output max to 10Amps current, support 12V & 5V peripheral equipment power s upply. Ultra low power design;

Unique UPS Technology ensures the integrity of record when power failure occurs, even can last for 8-10s.

HDD+SD Card Storage (Support 2.5" HDD, max 128G SD Card) protect from Shock & Dust damage ;support USB port data backup and device update;

Support 2 USB ports, data backup and equipment upgrades.

Support 9CH alarm input (1CH Analog input + 8CH IO alarm input),2CH Independent alarm output.

Support 2 CAN interface.

Support HDD heating functions, can work in harsh environment.

Support GPS/BD/G-Sensor Extension module;

Realize real-time monitor through 3G/4G;

Support Broadcast/Intercom/Text sent etc;can add oil sensor/temperature sensor/POS/LED Advertise ment Panel;

Support OTG device upgrade automatically, , device can automatically upgrade version update, main tenance is more convenient

Support IOS/Android Phone Remote monitor

High reliability aviation connectors, high cost performance, stable and reliable.

Product Features:

- \blacklozenge HIS Solution,H.264 Compression,multiple stream recording,support 5CH video input, video recording and playback (4CH real-
- time 720p million pixels Analog HD input /4CH analog standard definition input /2CH analog input +2CH HD mixed input +1CH 1080P network camera input);
- ♦ High quality real time recording, 720P/CIF/HD1/D1 Optional, quality adjustable;
- ◆ Professional Car Power Design,6-36V wide voltage,Provide reverse voltage/over-load/short circuit protection, to meet kinds of car application;
- ♦ Support 12VDC output voltage, power supply for Camera/Screen etc;
- ♦ Max 1TB HDD + 128GB SD Card Mirror Recording, protect DVR from shock & Dust damage;
- ♦ Watchdog abnormal restart function, protect SD Card and Record;
- ◆ Exclusive Pre-allocated Vehicle File System protect data completeness ;
- ♦ ACC Delay off, can set 24 hours;
- ♦ Unique UPS Technology ensures the integrity of record when power failure occurs, even can last for 10-15s.
- ♦ Auto Record/Manual Record/Alarm Record etc working mode to meet different requirements;

- ♦ Show Car status/Plate/Driving Route/Low Speed/Over Speed information for convenient managem ent:
- ◆ Support GPS/BD,3G/4G Module Optional,WIFI extend;
- ◆ Strong Network, device configure via IE Web, Support SMS Get device information and configure;
- ◆ Support Monitoring, Two-way Intercom, PTZ, Alarm, Overspeed, Geo Fence etc through remote control platform;
- ♦ 8CH IO Alarm input(Door Open,Light,Turn direction,brake,reverse etc),can linkage kinds of alarm;
- ♦ 2CH Alarm Output, Support Light and Sound alarm sensor, Oil/Power cut off;
- ♦ High level aviation interface, easily installation and better shockproof, more stable;
- ♦ Support Local Auto-photo when alarm input.
- ♦ High reliable aviation connectors input/output, easy installation, stronger anti-vibration.
- ◆ Easily Smart GUI Interface, saving time in device setting;
- lackloau Strong Stable Application, Support 3G/4G Real-time monitor, talk-back, playback, record, picture snap etc;
- ♦ Updated through SD or OTA Remote Automatic updating, more stable and convenient;
- ◆ Support Phone Remote Monitor, Phone Calling etc;
- ◆ Support PTZ/POS/Oil Sensor/LED Advertisement Panel etc;
- ♦ Support Ministry of Transport Standard Agreement
- ◆ Be Customized according your request;

Specification

Item		1	Parameter
os			Linux
Language			English/Chinese/Customized
Video Compression			H.264 Compression
OSD			Overlays information such as date time and vehicle ID
		r Interfa	Setup system parameters with the remote control.
	ce		
Video Record System	Video Input		4CH real-time 720p million pixels Analog HD input /4CH analog standard definition input/2CH analog input+2CH HD mixed input+ 1CH 1080P network camera input), aviation connector, 1.0Vp-p, 750
	Video Output		2CH CVBS output+1CH VGA output for optional,1.0Vp-p, 75Ω,Support 1CH Full Screen,4CH Screen view
	Preview		Support 1 channel and 4 channels preview, 5 channels splice preview Support Manual/Alarm Trigger full screen preview
	Resolution		1080P/720P/D1/HD1/CIF, MAX:4 channels of 720P + 1080P / 4 channels of D1
	Image Quality		1-4 levels, 1 is the highest level.
	Video Standaro		PAL: 100f/s , CCIR625 line,50field;
			NTSC: 120f/s, CCIR525 line,60field;
			CIF: 256Kpps ~ 1.5Mpps, 8 level video quality optional; HD1: 600Kpps ~ 2.5Mpps, 8 level video quality optional;
			D1: 800Kbps ~ 3Mbps, 8 level video quality optional; D1: 800Kbps ~ 3Mbps, 8 level video quality optional;
			720P: 4Mbps-6Mbps, multi level video quality optional
	Record Mode		The default setting is auto recording after power on. Timed recording, alarm trigger recording and manual recording are supported.
Audio	Audio Input		4CH Aviation Plug Input
	Audio Output		2CH,headphone connect at front panel, BNC Connect on Back panel
	Compression		G.726 compression, 8KB/s speed
Alarm Input			7CH Alarm Input, 1CH AD Input, impulse speed input, Alarm Linkage
Alarm Output			2CH Alarm Output, Support Light/Sound alarm sensor Oil/Power cut off
Interface			3CH RS232. POS/Fuel Sensor/LED Advertisement Connection
			2CH 485 Interface,Connect PTZ Camera
Wireless Transmission			Support Built in 3G transmission, WCDMA, CDMA2000,GPRS, EDGE[] Built in 4G module optional, TDD-ITE, FDD-ITE Built in 4G module optional, TDD-ITE, FDD-ITE
GPS Position			Sunt in 45 mount opinional, 10D-L1E, FDD-L1E Support Bull (FS/BD Module) Support Bull (FS/BD Module)
GPS Position HDD			Jupper Date of SJBD Froduite Max 2.5" HDD DD Max 2.5" HDD DD Max 2.5" HDD DD Max 2.5" HDD DD Max 3.5" HD
Storage	SD Card		Max 128GB SD Card Mirror Recording Keep Data Safety
Storage	Update		Support USB Updating, SD Card Updating, OTA Remote Updating
	File Format		Jupport of Departing, 3D citra optaining, 6TA remote optaining
	File System		Special FAT32 File System
	USB		Special PALSE THE System USB Interface on Front Panel for data back up by U Disk Hard Disk
Record Replay	Video Sea		USB Interface on Front Faller for data back up by U Disk, Hafti Disk Search By Record Time/Record Type etc
necoru nepiay	Playback		Max support 4CH Replay (Stop)Fast/Slow at same time
			wax support «Lri replay) stop) rasystow at same time Support forward and backward play at the speed of: \$2.x4_x8_x16.
Security			support toward and netsward to pay at the speed of: x z,x4,x6,x16. User/Admin 2 Level Different Password User/Admin 2 Level Different Password
	hr.:		USEF/AGMINI Z LEVEL DILBETENT PASSWORD SUPPORT VOICE CELL BEACH OF THE STANDARD STAN
Optional Functions			support voice can each other
		dcast	Support 115 voice producast function.
			Support LED Advertisement Pane TOil Sensor POS Bus Station Broadcaster Car OBD,ect.external device
	nd		Support 222 Autor anomalie a unocije i objeda odanom 20 odanom objeda odanom ina ubite
Voltage & Power			Wide Voltage. Support Timed/Delay off/ over-load/Reversing connection/voltage shortage/short circuit etc.
		ement	
		ut Volta	DC:+6V·+36V
1			+12V@1.5A[+5V@1.5A
1	age Pov		Westing COV
		wet.	Working []5W

Working Environment	Temperatur	-20°C - +70°C
	e	
	Humidity	20% - 80%
Ohters	Size	200 [DD* 187[]WD* 62[]H] mm
	Weight	1.90 Κα