



ation

-			
Item		Parameter	
OS		Linux	
Language		English/Chinese/Customized	
Video Compression		H.264 Compression	
OSD		Overlays information such as date time and vehicle ID	
GUI	Graphical User Interface	Setup system parameters with the remote control.	
Video Record System	Video Input	4CH 960P/720P AHD input,aviation connector, 1.0Vp-p, 75Ω	
	Video Onput	1 CVBS, 1.0Vp-p, 75Ω,Aviation,Support 1CH Full Screen,4CH Screen view	
	Preview	Support 1 channel and 4 channels preview., Support Manual/Alarm Trigger full screen preview	
	Resolution	720P/D1/HD1/CIF, MAX:4 channels of 720P and 4 channels of D1	
	Image Quality	 1-4 levels, 1 is the highest level. PAL: 100f/s, CCIR625 line,50field; NTSC: 120f/s, CCIR525 line,60field; CIF: 256Kbps ~ 1.5Mbps, 8 level video quality optional; HD1: 600Kbps ~ 2.5Mbps, 8 level video quality optional; D1: 800Kbps ~ 3Mbps, 8 level video quality optional; 720P: 4Mbps-6Mbps, multi level video quality optional 	
	Video Standard		
	Record Mode	The default setting is auto recording after power on. Timed recording, alarm trigger recording and manual recording are supported.	
Audio	Audio Input	4CH Aviation Plug Input	
	Audio Output	2CH,headphone connect at front panel, BNC Connect on Back panel	
	Compression	G.726 compression, 8KB/s speed	
Alarm Input		7CH Alarm Input,1CH AD Input,impulse speed input,Alarm Linkage	


Alarm Output		2CH Alarm Output,Support Light/Sound alarm sensor,Oil/Power cut off		
Interface		3CH RS232, POS/Fuel Sensor/LED Advertisement Connection		
		1CH 485 Interface,Connect PTZ Camera		
Wireless Transmission		Support Built in 3G transmission,, WCDMA, CDMA2000,GPRS, EDGE; Built in 4G module optional, TDD-LTE, FDD-LTE		
GPS Position		Support Built GPS/BD Module		
	HDD	Max 2.5" 1TB HDD		
Storage	SD Card	Max 128GB SD Card Mirror Recording Keep Data Safety		
-	Update	Support USB Updating, SD Card Updating, OTA Remote Updating		
	File Format	H.264		
	File System	Special FAT32 File System		
	USB	USB Interface on Front Panel for data back up by U Disk,Hard Disk		
Record Replay	Video Search	Search By Record Time/Record Type etc		
	Playback	Max support 4CH Replay /Stop/Fast/Slow at same time		
		Support forward and backward play at the speed of: x 2,x4,x8,x16.		
Security		User/Admin 2 Level Different Password		
Optional Functions	Voice Call	Support voice call each other		
	TTS Voice Broadcast	Support TTS voice broadcast function.		
	Serial Expand	Support LED Advertisement Panel,Oil Sensor, POS,Bus Station Broadcaster,Car OBD,ect.external device		
Voltage & Power Management Wide Voltage.		ement Wide Voltage.Support Timed/Delay off		
	Input Voltage	DC:+6V - +36V		
	Output Voltag	e +12V~1.5A,+5V~1.5A		
	Power	Working <5W		
Working Environment	Temperature	-20°C - +70°C		
	Humidity	20% - 80%		
Ohters	Size	200 (D)* 187(W)* 62(H) mm		
	Weight	1.90 Kg		

Our Services



PC&Phone Monitoring







hand

CMSV6 In Mobile Phone Have all in the palm of your

Real-time monitoring via Mobile Phone Support iPhone, Android, iPad system

	SAMEUNG	•
4 86	হ া 81	% =: 9:45
Ø,		
1010	110110111101	
	1001011111000	
	001101100	
010100	1010	21
	- The	XIN
	_	
胀号:	RCM	•
	RCM	v
密 码:		v
	124.228.174.201:8088	v
密 码:		v
密 码:	124.228.174.201:8088	¥
密 码:	······ 124.228.174.201:8088 ✓ 记住密码 自动登录	*



Video & Audio M	onitoring Online Vehicle	GPS
Satellite Map	Video Storage	
PTZ control Snapshot Voi	Tracking Display ice intercom	Picture

FQA

- Q: During playback, the map doesn't show?
- A: Possible reasons are as follows;
- 1.Net cable did not connect to PC;
- 2.Net works, but the computer can not get to the Internet;
- Q: When SD card and HDD records, How is the record coverage?
- A: SD card and HDD will record circularly for each other. When they are full, they

will delete the original video records respectively.

Q: The device was opened, HDD was installed, but the device can not record successful. A: 1.Check the HDD/SD Card was formatted or not, the unformatted HH/SD Card can not be used. Enter into the Main Menu – System Setup – Formatting the new installed HDD/SD Card.

2. If the recording channel is closed, if set the timing recording, it can not recording when it beyond the period of timing recording.

3. If the HDD is connect well, if the HDD/SD light is on.



Richmor Brand Package

Standard Package

×

Shipping

Strong cooperated with DHL/UPS Etc for fast and safety delivery.

- a. 2-5 days after payment cleared for sample order.
- b. 5-10 days after payment cleared depends on order quantity for bulk order.

Payment



Exhibition

Richmor

CPSE2012 in Shenzhen





CPSE2012-- Guangdong TV Report-Shenzhen Richmor



Certifications



Skype:rcmcctvsales5 Mobile/WhatsApp:+86-18126263838