



terms.	Device parameters	Performance index		
Name	Product Name	4 Channel Mobile DVR(HDD & SD Storage)		
System	Operation System	Linux		
	Operation Interface	Graphical Interfaces, Chinese English optional		
	File System	Proprietary Format		
	System Privileges	Deer Password		
Video	Video Ispat	6ch SSI Independent Input: 1.6Vp-p[75Ω Both B&W a Color Cameras		
	Video Output	I Chazzel PAL/NTSC Output, 1.8Vp-p[7502] Composite Video Signal		
	Video Display	1 Or 4 Screen Display		
	Video Standard	PAL 25frames Sec NTSC 30frames Sec		
	System Resources	241-100 Frames, NTSC 130 Enumer		
	Nadio Input	Two Chappels Independent Input, 5000		
	Nadio Output	1 Chappel/4 Chappels Cap Se Convert Freels)		
Andio	Basic Output Level	1.0-2.2V		
ALIIGAS	Distortion Plus Noise	s-35dB		
	Recording Mode	Sound And Image Synchronization		
	Nadio Compression	ADRCH		
Alarm	Varn is	4 Chappels Independent Input, High Voltage Tripper		
	Nam out	2 Channels Independent output		
	More Detect	entibble		
Network Interface	sc .	Can Expand One WCDMA or CDMA2000 Module Inside		
CIPS Interface	SPS	Can Expand GPS Module inside		
Extend Interface	Intercom	Can Expand Intercom Module Inside		
Others	Power Consumption	DOI-36V 5% #16W		
	Working Temperature	20°C - +85°C x80%		
	Clock	Built-In Clock, Calendar		
Packaging	Product Size	220(L)*193(W)*53(H)mm[with Holder]		
	Product Net Weight	L2KG/without HDD1		













