4ch sd card mobile dvr Support HDD heating functions and GPS 3G Module



Richmor

WE PUT FORWARD THE IDEAL OF "4M" IN ENTERPRISE MANAGEMENT:

- More enhancements of product quality everyday.
- More progress of services and sales everyday,
- More widely the effect of our brand expands everyday,

More smiles to each of us everyday.

product specification:


| Item | | parameter |
|------------------------|--------------------------|---|
| Operating System | | Linux |
| Language | | English/chinese/customized |
| Video Compres | sion | H.264 Compression |
| OSD | | overlays information such as date time and vehicle ID |
| GUI | Graphical user interface | setup system parameters with the remote control |
| | video input | 4CH 960P/720P AHD input,aviation connector, 1.0Vp-p, 75Ω |
| | video output | 1 CVBS, 1.0Vp-p, 75Ω, Aviation, Support 1CH Full Screen, 4CH Screen view |
| | preview | Support 1 channel and 4 channels preview., Support Manual/Alarm Trigger full screen preview |
| | resolution | 720P/D1/HD1/CIF, MAX:4 channels of 720P and 4 channels of D1 |
| Video Record System | image quality | 1-4 levels, 1 is the highest level. |
| | video standard | PAL: 100f/s , CCIR625 line,50field; NTSC: 120f/s, CCIR525 line,60field; CIF: 256Kbps ~ 1.5Mbps, 8 level video quality optional; HD1: 600Kbps ~ 2.5Mbps, 8 level video quality optional; D1: 800Kbps ~ 3Mbps, 8 level video quality optional; 720P: 4Mbps-6Mbps, multi level video quality optional |
| | record mode | The default setting is auto recording after power on. Timed recording, alarm trigger recording and manual recording are supported. |
| Audio | audio input | 4CH Aviation Plug Input |
| | audio output | 2CH, headphone connect at front panel, BNC Connect on Back panel |
| | compression | G.726 compression, 8KB/s speed |
| Alarm Input | | 7CH Alarm Input,1CH AD Input,impulse speed input,Alarm Linkage |
| Alarm Output | | 2CH Alarm Output, Support Light/Sound alarm sensor, Oil/Power cut off |

| Interface | | 3CH RS232, POS/Fuel Sensor/LED Advertisement Connection |
|---|---|---|
| Interface | | 1CH 485 Interface, Connect PTZ Camera |
| Wireless Transmi | ssion | Support Built in 3G transmission,, WCDMA, CDMA2000,GPRS, EDGE; Built in 4G module optional, TDD-LTE, FDD-LTE |
| GPS Position | | Support Built GPS/BD Module |
| | HDDMax 2.5" 1TB HDDSD CardMax 128GB SD Card Mirror Recording Keep DataupdateSupport USB Updating, SD Card Updating,OTA Refile formatfile formatH.264file systemSpecial FAT32 File SystemUSBUSB Interface on Front Panel for data back up byvideo searchSearch By Record Time/Record Type etcplaybackMax support 4CH Replay /Stop/Fast/Slow at same Support forward and backward play at the speedSecurityUser/Admin 2 Level Different Password | Max 2.5" 1TB HDD |
| | SD Card | Max 128GB SD Card Mirror Recording Keep Data Safety |
| Storage | update | Support USB Updating, SD Card Updating, OTA Remote Updating |
| Storage | file format | H.264 |
| | file system | Special FAT32 File System |
| HDDStorageHDDStorageSD Cardupdatefile formatfile systemUSBUSBvideo searchRecord ReplayplaybackSecurityvoice callOptionalTTS Voice broadcastFunctionsserial expandVoltage & PowerOutput VoltageVorkingTemperatureEnvironmentHumidityOthersSize | USB Interface on Front Panel for data back up by U Disk, Hard Disk | |
| | video search | Search By Record Time/Record Type etc |
| Record Replay | nlavhaola | Max support 4CH Replay /Stop/Fast/Slow at same time |
| | раураск | Support forward and backward play at the speed of: x 2,x4,x8,x16. |
| Securi | ty | User/Admin 2 Level Different Password |
| | voice call | Support voice call each other |
| Optional | TTS Voice broadcast | Support TTS voice broadcast function. |
| Functions | serial expand | Support LED Advertisement Panel,Oil Sensor, POS,Bus Station Broadcaster,Car OBD,ect.external device |
| | Dowor Managament | Wide Voltage.Support Timed/Delay off |
| | | DC:+6V - +36V |
| Voltage & Power | | |
| | | +12V~1.5A,+5V~1.5A |
| | | Working<5W |
| | · · | -20°C - +70°C |
| Environment | - | 20% - 80% |
| Others | | 200 (D)* 187(W)* 62(H) mm |
| | Weight | 1.90Kg |


Product Show:








Client User Graph Interface



our mdvr support mobile Client monitoring like PC, mobile phone etc.



Appliacation

FUNCTIONS

- Video& Audio real-time monitoring
- Online Vehicle Status
- Satellite Map
- GPS
- Video Storage
- Tracking Display
- Intercom
- Fuel Sensor
- G-Sensor
- Temperature-Sensor



certificate



company and factory






Richmor OEM & ODM Service Brasil World Cup Supplier



Exhibition:

Richmor

CPSE2012 in Shenzhen



CPSE2012-- Guangdong TV Report-Shenzhen Richmor



Other kinds of products



If u r interested in our dvr, pls contact Amily: whatsapp--18929314790

系统配套产品 VEHICLE CAMERA PARAMETER

车载红外半球摄像机 Vehicle Dome IR Camera



| RCM-D342S/IR | 1/3" SONY CCD 420TVL 0.5LUX 24 units ¢5 LED or 10 Units ¢8 LED | 3.6mm/6mm |
|--------------|---|-------------|
| RCM-D442A/IR | 1/4" Sharp CCD 420TVL 0.5LUX 24 Units ©5 LED or 10 units ©8 LED | 2.8mm/3.6mm |
| RCM-D348S/IR | 1/3" SONY CCD 480TVL 0.1LUX 24 Units ©5 LED or 10 units ©8 LED | 3.6mm/6mm |
| RCM-D354S/IR | 1/3" SONY CCD 540TVL 0.1LUX 24 Units ©5 LED or 10 Units ©8 LED | 3.6mm/6mm |
| RCM-D360S/IR | 1/3* SONY CCD 600TVL 0.1LUX 24 Units ©5 LED or 10 Units ©8 LED | 3.6mm/6mm |
| RCM-D370S/IR | 1/3" SONY CCD 700TVL 0.1LUX 24 Units ©5 LED or 10 Units ©8 LED | 3.6mm/6mm |

车载红外防水摄像机 Vehicle IR Waterproof Camera



| proor Gamera | | |
|---------------|---|-----------|
| RCM-CM442A/IR | 1/4" Sharp CCD 420TVL 0.5LUX 20 Units © 5 LED (Work Under water) | 3.6mm/6mm |
| RCM-CM342S/IR | 1/3" SONY CCD 420TVL 0.1LUX 20 Units © 5 LED (Work under Water) | 3.6mm/6mm |
| RCM-CM348S/IR | 1/3" SONY CCD 480TVL 0.1LUX 20 Units ¢5 LED (Work Under Water) | 3.6mm/6mm |
| RCM-CM360S/IR | 1/3" SONY CCD 600TVL 0.1LUX 20 Units © 5 LED (Work Under Water) | 3.6mm/6mm |



Best Regards Amily Zhang

HAND US YOUR TRUST, OFFER YOU OUR BEST!!! Shenzhen Richmor Technology Development Co.,LTD

Email: <u>overseasales-2@rcmcctv.com</u> Skype: rcmcctvsales2 QQ: 2355778097 MB/Whatsapp: +86 18929314790 Website: http://www.richmor.net/ ADD: 6th Floor, F Building, Xinzhi Industrial Park, Yangmei,Bantian,Longgang, Shenzhen

