# AHD vehicle dvr wth 4channels 720P resolution input GPS tracking with fuel sensor for truck surveillance





Item		Parameter
OS		Linux
Language		English/Chinese/Customized
Video Compression		H.264 Compression
OSD		Overlays information such as date time and vehicle ID
GUI	Graphical User Interface	Setup system parameters with the remote control.
Video Record System	Video Input	4CH 720P AHD input/SD input/mixed input, aviation connector, 1.0Vp-p, 75Ω
	Video Output	2CH CVBS+ VGA output for optional, 1.0Vp-p, 75Ω,Aviation,Support 1CH Full Screen, 4CH Screen view
	Preview	Support 1 channel and 4 channels preview., Support Manual/Alarm Trigger full screen preview
	Resolution	720P/D1/HD1/CIF, MAX:4 channels 720P and 4 channels D1
	Image Quality	0-7 levels, 0 is the highest level.
	Video Standard	PAL: 100f/s, CCIR625 line,50field; NTSC: 120f/s, CCIR525 line,60field; CIF: 256Kbps ~ 1.5Mbps, 8 level video quality optional; HD1: 600Kbps ~ 2.5Mbps, 8 level video quality optional; D1: 800Kbps ~ 3Mbps, 8 level video quality optional; 720P: 4Mbps-6Mbps, multi level video quality optional
	Record Mode	The default setting is auto recording after power on. Timed recording, alarm trigger recording and manual recording are supported.

Audio	Audio Input	4CH Aviation Plug Input
	Audio Output	2CH,headphone connect at front panel,
		BNC Connect on Back panel
	Compression	G.726 compression, 8KB/s speed
Alarm Input		7CH Alarm Input,1CH AD Input,
		impulse speed input,Alarm Linkage
Alarm Output		2CH Alarm Output, Support Light/
		Sound alarm sensor,Oil/Power cut off
Interface		3CH RS232, POS/Fuel Sensor/
		LED Advertisement Connection
		2CH 485 Interface,Connect PTZ Camera
		2CH CAN interface
Wireless Transmission		Support Built in 3G transmission,
		WCDMA, CDMA2000,GPRS, EDGE
		Built in 4G module optional, TDD-LTE, FDD-LTE
GPS Position	T	Support Built GPS/BD Module
	HDD	Max 2.5" 2TB HDD
Storage	SD Card	Max 128GB SD Card Mirror Recording Keep Data Safety
	Update	Support USB Updating, SD Card Updatin, OTA Remote Updating
	File Format	H.264
	File System	Special FAT32 File System
	USB	USB Interface on Front Panel for
D 1 D 1	Video Cerrel	data back up by U Disk,Hard Disk
Record Replay	Video Search	Search By Record Time/Record Type etc
	Playback	Max support 4CH Replay /Stop/Fast/Slow at same time
		Support forward and backward
Coourity		play at the speed of: x 2,x4,x8,x16.  User/Admin 2 Level Different Password
Security Ontional Functions	Voice Call	·
Optional Functions		Support voice call each other
	Serial Expand	Support LED Advertisement Panel□Oil Sensor□ POS□Bus Station Broadcaster□ Car OBD,ect.external dev
		ice
Voltage & Power	Power Management	Wide Voltage.Support Timed/Delay off
	Input Voltage	DC:+6V - +36V
	Power	Working □5W
	Temperature	-20°C - +70°C
Working Environment	Humidity	20% - 80%
	Size	200 [D[]* 187[]W[]* 62[]H[] mm
Others	Weight	1.90 Kg

## **Main Features**

1. **HIS Solution,H.264 Compression,support 4CH 720P AHD input**/ 4CH analog standard definiti on Camera input/2CH HD + 2CH SD mixed input;

- 2. 3CH video output (2CH CVBS video, support front&rear panel output; VGA output for optional.)
- 3. Exclusive pre-


allocate File System protect data completeness, prevent SD Card fragment, ensure date stablely and c ompletely.

- 4. 8-36V wide voltage with low power consumption.
- 5. Unique UPS Technology ensures the integrality of record when power failure occurs, even can for 8-10s.
- 6. HDD+SD Card Storage (Support 2.5" HDD, max 128G SD Card) protect from Shock & Dust damage ;support USB port data backup and device update;
- 7. Support 2 USB interfaces, data backup and device upgrade.
- 8. Support 9CH alarm input (1CH analog input + 8CH IO alarm input ), 2CH independent alarm output.
- 9. Support 2 CAN interfaces.
- 10. Support HDD heating functions, can work in harsh environment.
- 11. Support GPS/BD/G-Sensor Extension modul;
- 12. Realize real-time monitor through 3G/4G;
- 13. Support **WIFI module**, can download data automatically.
- 14 Support Broadcast/Intercom/Text sent etc;can add oil sensor/temperature sensor/POS/LE **D** Advertisement Panel;
- 15. Support SMS remote configure/ control device;
- 16. OTA(On-The-
- Air) Device automatically upgrade function, can upgrade to updated version, maintenance is more convenient.
- 17. Support voice call function.
- 18. Support IOS/Android Phone Remote monitor


#### PC Software interface for gps tracking



### **Android/IOS APP Monitor**




#### Server software interface



## **Application**





**Good Relationship with our Customers** 









For more information pls feel free to contact Amily:

**Email:** overseasales-2@rcmcctv.com

**Skype:** rcmcctvsales2

QQ: 2355778097

**MB/whatsapp:** +86 18929314790