

RICHMOR PRODUCTS FEATURES

- 1. Power failure protection.**
 - 2. Wide voltage.**
 - 3. OTA function support. (Upgrading DVR software automatically, better after-sales service for you, ONLY WE CAN ACHIEVE IT IN CHINA FOR NOW.)**
 - 4. A SMS can get DVR situation feedback from DVR.(ONLY WE CAN ACHIEVE IT IN CHINA FOR NOW.)**
 - 5. Industrial level design. (More professional and better quality.)**
 - 6. Modular design. (To prevent a module error while affecting the entire product.)**
 - 7. Encrypt video format. (To prevent data loss)**
 - 8. Current and voltage over protection.**
 - 9. Wide working temperature. (-25°C- +75°C).**
 - 10. Data redundancy technology. (To prevent data loss)**
 - 11. Excellent vibration protection.**
-



SMS Device configure
OTA Remote Updating
AHD 720P/960P
Motion Detection

Richmor





RCM-MDR210 Parameter Sheet

Item	Parameter
OS	Linux
Language	Chinese/English/Customized
Video Compression	H.264
OSD	Overlays information such as date time and vehicle ID
GUI	Graphical User Interface Setup system parameters with the remote control.
Video Record System	4CH 720P AHD input,aviation connector, 1.0Vp-p, 75Ω
Video Output	1 CVBS, 1.0Vp-p, 75Ω,Aviation,Support 1CH Full Screen,4CH Screen
Preview	Support 1 channel and 4 channels preview.,Support Manual/Alarm Trigger full screen preview
Resolution	720P/D1/HD1/CIF, MAX:4 channels of 720P and 4 channels of D1
Video Quality	1-4 levels, 1 is the highest level.
Video Standard	PAL: 100f/s , CCIR625 line,50field; NTSC: 120f/s, CCIR525 line,60field; CIF: 256Kbps ~ 1.5Mbps, 8 level video quality optional; HD1: 600Kbps ~ 2.5Mbps, 8 level video quality optional; D1: 800Kbps ~ 3Mbps, 8 level video quality optional; 720P: 4Mbps-6Mbps, multi level video quality optional
Audio	Record Mode Audio Input Audio Output Compression The default setting is auto recording after power on. Timed recording, alarm trigger recording and manual recording are supported. 4CH ,Aviation Plug 1CH,Aviation Plug G.726 compression, 8KB/s speed
Alarm Input	3Ch Alarm Input, kinds of alarm linkage support
Alarm Output	1CH Alarm Output
Position	Support Built GPS/BD Module
G-Sensor	Support G-sensor
Storage	SD Upgrade File Format File System Dual SD Card,each max 128GB SD Card loop recording Support SD Card updating .H264 Special FAT32 File System

Video Playback	Video Search Playback	Search By Record Time/Record Type etc Max support 4CH Replay /Stop/Fast/Slow at same time Support forward and backward play at the speed of: x 2,x4,x8,x16.
Voltage & Power	Power Management Voltage Input Voltage Output Power Consumption	Wide Voltage.Support Timed/Delay off DC:+10V ~ +36V +12V~2.5A,+5V~2.5A Normal Working <5W
Working Environment	Temperature Humidity	-20°C to +70°C 20% to 80%
Security others	Password Size Net Weight	User/Admin 2 Level Different Password 112(W) x36(H) x138(D) mm 360g


Player software interface



Application

Widely used in passenger car,bus,taxi,school bus,lorry,dangerous vehicle, personal car and ship etc.





Buying Guides

Packaging

1 unit with all standard accessories such as AV Cables/IO Cable/Power Cable/Key etc

Neutral paper box or Color paper box with Logo Richmor printed,also welcome customized package.



Richmor Brand Package



Standard Package

Shipping

Strong cooperated with DHL/UPS Etc for fast and safety delivery.

- a. 2-5 days after payment cleared for sample order.
- b. 5-10 days after payment cleared depends on order quantity for bulk order.

Payment



Service

1. Well Trained Sales team and engineers for fast and professional support

2. OEM/ODM Service



CUSTOMER SATISFACTION

- Excellent Aftersale service
- 12 months warranty
- 24 hours customer service
- We understand the importance of our customers

Exhibition

CERTIFICATE OF CONFORMITY



CERTIFICATE

of Conformity

(0119920) Inspection of Hazardous Substances

Reference No.: L151100410208116

When tested as specified, the following sample complies with the requirements of Commission Decision of 21 July 2010 amending Directive 2011/65/EU.

Applicant:	Shenzhen Weichuan Technology Development Co., Ltd.
Address:	#F No.84 West Longgang Road, Longhua New District, Shenzhen, China
Trade Mark:	Weichuan
Product:	Mobile Phone
Material:	PCW MEDIUM, PCW MEDIUM, PCW MEDIUM, PCW MEDIUM, PCW MEDIUM, PCW MEDIUM

The test report is issued to the Company subject to its General Conditions of Service printed on the last sheet of this report. Information and/or identification and/or identification number address (name). The results shown in this test report apply only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, copied or full without prior written permission of the Company.

Other relevant documents have to be obtained.

RoHS



Manager

April 16, 2015

Shenzhen CCS Compliance Testing Laboratory Ltd

10, Xiangyuan Industrial Park, Xiangyuan Road, Baoan District, Shenzhen, Guangdong, China

Tel: 0086-755-8308-1100

http://www.ccs.com.cn

Fax: 0086-755-8308-1102

Email: shenzhen@ccs.com.cn

Richmor

CPSE2012 in Shenzhen



CPSE2013

10.29-10.31

4 Booth we have

Welcome you !!!



CPSE2012-- Guangdong TV Report-Shenzhen Richmor



About us&Customers:



Inner Training after study from Alibaba in July



Technical Training For Fast Response to Customer **Richmor 锐驰**



lecturer for Execution



South Africa




Argentina



Czech Republic



Brazil



Russia



India



Turkey



Mexico



Saudi Arabia

Skype: rcmcctvsales2