

Richmor Portable Video Recorder with 3G GPS WIFI For Brasil World Cup

RCM-SP5800

Richmor Portable Video Recorder Advantage

- 1.**3G GPS WIFI** G-sensor TF Card **Portable DVR**;
- 2.**SOS Button** for Alarm Recording;
- 3.**Picture snap button**;
- 4.PTT Function,device and device communication;
- 5.Intercom Function,officer and police communication;
- 6.8 Hours working time

Picture



Parameter		
Items	Device parameters	Performance index
System	Operation system	Linux
	Separate design	Main device: work independently to realize local record Auxiliary device: GPS / 3G, backup battery
	Graphic operation interface	Use buttons to complete the setting of various parameters
	Security management	User password management

Video	Video input	Built-in camera lens, angle of visibility: 70°, CMOS sensor
	OSD	Time & date, device ID, GPS, etc.
	Compression	H.264. Hisilicon high performance processor is adopted.
	Video resolution	VGA by default, QVGA optional
	Video Bit rate QVGA	QVGA: 400Kbps ~ 1.5Mbps, 4 levels of bit rate optional
	Video Bit rate VGA	VGA: 1000kbps ~ 2Mbps, 4 levels of bit rate optional
	Preview function	Real time, record video preview
	Dual stream	Support
Audio	Audio input	Built-in MIC
	Audio output	Built-in speaker, >1W
	Compression	G.726
Recording	Storage media	Micro-SD card, support 1G ~ 32G
	File format/system	ASF record file format, FAT32 file system
	Recording mode	Startup recording by default, support manual recording
	Recording search	Search recording video files by time, type, etc.
	Recording Playback	Support fast forward, fast backward, play, pause, support 2, 4, 8, 16 times speed fast forward or fast backward, support playback of file by time
USB Interface	Host Access	Can Expand One For USB Disk Backup
Network interface	Wireless transmission	Built-in 3G wireless transmission module, WCDMA, CDMA2000, TD-SCDMA system optional; Compatible with GPRS, EDGE;
Extend Interface	Intercom	Can Expand Intercom Module Inside
Screen parameters	Size	2.4 inch
	Type	TFT
	Resolution	480*234
Upgrade	System upgrade	Support Micro-SD card upgrade
Working environment	Temperature	-20°C ~ +50°C
	Humidity	20% to 80%
Dimension	Main device	50(W) x90(H) x28(D) mm
	Auxiliary device	70(W) x110(H) x28(D) mm
Weight	Main device	Net weight: 95g, Gross weight: 307.5g
	Auxiliary device	Net weight: 238g, Gross weight: 352g



Package



Richmor Brand Package



Standard Package

Certification

CERTIFICATE OF CONFORMITY

	
CERTIFICATE of Conformity (SYSTEM) Reduction of Hazardous Substances	
Reference No.: L151294102818	
When taken as specified, the submitted sample conforms with the requirements of Commission Decision of 21 July 2007 amending Directive 2002/95/EC.	
Applicant:	Boschert Robotics Technology Development Co., Ltd.
Address:	JF 30-3A West Longgang Road, Longhua New District, Shenzhen, China
Third Party:	Robostar
Product:	Gemini 303R
Material:	NICK-MODUL, RUM-MODUL, RUM-MODUL, RUM-MODUL, ROM-MODUL, ROM-MODUL, ROM-MODUL
The test report is issued by the Company subject to its general conditions of service being accepted. Attention is drawn to the limitations of liability, indemnification and subcontracting rules outlined therein. The results shown in this test report apply only to the material(s) tested under defined conditions. This Test Report cannot be repeated without it fully authorizing your written permission of the Company.	
Other relevant documents have to be obtained.	
RoHS	
 <i>[Signature]</i> Manager April 08, 2012	
Description: L1512 Compliance Testing Laboratory Ltd. 15 Hongkong Industrial Estate, Tsinggi Road, Kowloon District, Shenzheng, Guangdong, China Tel: +86-755-83292436 http://www.l1512.com.cn/	
Fax: +86-755-83292437 E-Mail: shenzhen@l1512.com.cn	

Customer Visit


South Africa



Argentina



Czech Republic



Brazil



Turkey



Saudi Arabia

