product specifications

	or specifications				
Item		parameter			
Operating System		Linux			
Language		English/chinese/customized			
Video Compression		H.264 Compression			
OSD		overlays information such as date time and vehicle ID			
GUI	Graphical user interface	setup system parameters with the remote control			
Video Record System	video input	4CH 960P/720P AHD input, aviation connector, 1.0Vp-p, 75Ω			
	video output	1 CVBS, 1.0Vp-p, 75Ω, Aviation, Support 1CH Full Screen, 4CH Screen view			
	preview	Support 1 channel and 4 channels preview., Support Manual/Alarm Trigger full screen preview			
	resolution	720P/D1/HD1/CIF, MAX:4 channels of 720P and 4 channels of D1			
	image quality	1-4 levels, 1 is the highest level.			
	video standard	PAL: 100f/s , CCIR625 line,50field; NTSC: 120f/s, CCIR525 line,60field; CIF: 256Kbps ~ 1.5Mbps, 8 level video quality optional; HD1: 600Kbps ~ 2.5Mbps, 8 level video quality optional; D1: 800Kbps ~ 3Mbps, 8 level video quality optional; 720P: 4Mbps-6Mbps, multi level video quality optional			
	record mode	The default setting is auto recording after power on. Timed recording, alarm trigger recording and manual recording are supported.			
Audio	audio input	4CH Aviation Plug Input			
	audio output	2CH, headphone connect at front panel, BNC Connect on Back panel			
	compression	G.726 compression, 8KB/s speed			
Alarm Input		7CH Alarm Input,1CH AD Input,impulse speed input,Alarm Linkage			
Alarm Output		2CH Alarm Output,Support Light/Sound alarm sensor,Oil/Power cut off			
Interface		3CH RS232, POS/Fuel Sensor/LED Advertisement Connection			
		1CH 485 Interface,Connect PTZ Camera			

product show



Factory Audit SMS Device configure

OTA Remote Updating

8CH Full D1 Real time monitor

2TB HDD + 128GB SD Card

Richmor

OEM/ODM Customized **Factory Price** Independent R&D Tech Low Mog





System Structure



FUNCTIONS

- Video& Audio real-time monitoring
- Online Vehicle Status
- Satellite Map
- GPS
- Video Storage
- Tracking Display
- Intercom
- Fuel Sensor
- G-Sensor
- Temperature-Sensor



OEM & ODM Service

Brasil World Cup Supplier www.rcmcctv.com



Truck Coach



School Bus Bus



Police Car Taxi



Support All Vehicles

(1)FAQ:

Q:Are you factory manufacturer or trade company?

A:We are factory manufacturer,we have our own factory and technology/skill support,we have engineers to support/take charge of R&D ,resolve problems product.

Q: Does the MDVR support Hard drive and SD card?

A: Yes, HDD version MDVR supports SSD, HDD, and SD card. SD card version MDVR supports max 2 SD card.

The storage capacity can be from 32GB to 2TB.

2.Q: Is it difficult to install MDVR into the vehicle?

A: Actually it is easy to install it into vehicle. Most driver can figure out how to connect the power cables. And the camera installation is more easy. Just screw, connect and mount on the target place inside the vehicle.

3.Q: If I need door open and close alarm, overspeed alarm, reverse video, brake video, left-turn video, right-turn video, etc,is it available?

A: Definitely yes!

The I/O RS232 and 485 extension port is for all expanded purposes, including the functions above. In fact, there are more customized functions which can be connect through this port, such as Fuel sensor, Counter system,PTZ camera, and so on.

4.Q: We have our own platform and server, can we use your MDVR? Do you have SDK or can you do customized platform for us?

A: Yes, we have SDK ready and welcome your OEM customized order!

5.Q: I ever bought MDVR from other supplier. But the anti-vibration is not strong. Now the MDVR works bad and video recording is not good. I am adfraid to buy again.



contact person:Susie Zhou skype:rcmcctvsales4 mobile/whatapp:86-18126263832