

Newest Police Body Worn Camera infrared waterproof portable DVR Packaging & Delivery

Packaging Details:	Color Box/ Carton Box
Delivery Detail:	3~5 work days for sample order



Main Features

- 1) 2.4 inch Color Display Built-in;
- 2) 2100mAh large Capacity Li-ion Battery;
- 3) Full D1 Real-time Video & Audio Recording;
- 4) Max. 128GB Micro-SD Card Supported;
- 5) Built-in GPS Module.
- 6) 2-way audio, supports PTT talkback;
- 7) 3G/ 4G Remote View on PC or Smartphone;
- 8) Built-in Wi-Fi Module.

Specifications

Operating System	Linux	
Security Management	Administrator Password	
Video and Preview	Video Input	External Camera, Above 70 degree View Angle
	OSD	Time/ Date/ Device ID/ GPS
	Video Compression	H.264 Compression Coding
	Dual-Stream	Supported
	Resolution	D1/ HD1/ CIF Selectable
Audio	Audio Input	External Microphone
	Audio Compression	G.726 coding
Recording	Storage Medium	Micro-SD card(1G ~ 128G)
	File Format/ System	ASF/FAT32
	Record Mode	Auto Recording after Startup
	Video Searching	Search by Date/ Time
	Playback	Local Playback; Support 2/ 4/ 8/ 16 Times Fast forward/ Backward
TFT Display	Size	2.4 inch LCD
	Resolution	480*234
Wireless Transmission	3G Module Built-in (4G Optional)	
Wi-Fi	built-in WIFI module	

GPS	built-in GPS Module	
System Upgrading	Upgrading from TF Card	
Power Supply	Battery Capacity	Li-ion Battery, 2100mAh, 7.4V
	Charging Time	Less than 3 hours
	Working Hour	Above 4 hours
Operating Environment	Temperature	-20°C~+50°C
	Humidity	20% to 90%
Dimensions	65(W) x130(H) x30(D) mm	
Three Proofings	Grade: IP54	
Weight	Net: 475 g, (1.05LB)	

Product Showcase





Client Software

Mobile monitoring and management platform

The screenshot displays the 'Mobile monitoring and management platform' interface. The top navigation bar includes 'System', 'Video', 'Map', 'Playback', 'System Set', 'Log Query', and 'External App'. The main area is divided into several sections:

- Left Panel:** A tree view showing 'Monitor Center(5/12)' with a list of vehicle IDs including 桂A7586, 桂C27762, 桂D83568, 桂C28032, 桂C A6446, 80319, 桂A2001, 桂A7507, 桂A7509, 桂A7509, 桂A0024, and 桂A8017.
- Map:** A map of China with a green pin on a vehicle in the eastern region. Labels in Chinese identify '欧洲' (Europe), '亚洲' (Asia), '非洲' (Africa), '印度洋' (Indian Ocean), '太平洋' (Pacific Ocean), and '大洋洲' (Oceania).
- Vehicle Details:** A table with columns: Device, Positioning Time, Position, Speed, Alarm, Status. The first row shows: Device: 桂C27762, Positioning Time: 2015-05-11 10:11:49, Position: 福建省漳州市龙文区(闽南高速公路), Speed: 0.00 km/h(Northwest), Alarm: (blank), Status: (blank).
- Bottom Panel:** A status bar showing 'Running: 02:00:01', 'Online 5', 'Number of set loss 0', 'Alarms 0', 'Total 12', 'Live Ratio: 41.67%', and 'Lost Ratio: 58.33%'.

Mobile monitoring and management platform

The screenshot displays the 'Mobile monitoring and management platform' interface, specifically the 'System Parameters' configuration screen. The top navigation bar is identical to the first screenshot. The main area is divided into several sections:

- Left Panel:** A tree view showing 'Monitor Center(5/12)' with the same list of vehicle IDs as the first screenshot.
- System Parameters:** A configuration panel with the following settings:
 - Software starts automatically login
 - Language:
 - UI Style:
 - Exit System: No Operation Condition
 - Image Capture:
 - Location: (MC Indicates variable loss)
 - GPS update time: (Unit: s/2-100)
 - ID name: Enable
 - Default choose all online equipment
 - Enable multi-screen mode
 - Effect on call display
 - Deploy the vehicle of the day
- Bottom Panel:** A status bar showing 'Running: 00:00:15', 'Online 5', 'Number of set loss 0', 'Alarms 0', 'Total 12', 'Live Ratio: 41.67%', and 'Lost Ratio: 58.33%'.



Applications



Welcome to contact RICHMOR for more details!

Skype:rcmctvsales5

WhatsApp: +86-18126263838